

CIRCLE 2.5
DIRECT/INDIRECT



CERTIFICATIONS & COMPLIANCE




FEATURES



PERFORMANCE

- Up to 112lm/W efficiency
- 500 / 750lm/ft
- CRI > 80 & CRI > 90
- Damp rated




MOUNTING

Pendant



WHAT SHAPES YOU?

Combines with the BASO 2.5 system components



Catalog Number Example

CIRCLE 2.5-PDT-WH-OPOP-40K-C90-UNV-010V-0500LF-0500LF-DC-DM-72IN

A	B	C	D	E	F	G	H	I	J	K	L
---	---	---	---	---	---	---	---	---	---	---	---

A RANGE

CIRCLE 2.5 C I R C L E 2 . 5

B MOUNTING

Pendant P D T

pendant suspension set includes cable
suspension and one white power feeder
with a white junction box cover

for black power feeds or junction box
covers, please contact customer service

C COLOR

White	W H
Black	B L
Gray	G R
Custom color RAL	X X

recessed version available in white only

D LENS

OPOP opal cover direct O P O P
opal cover indirect

E CCT

2700 K	2 7 K
3000K	3 0 K
3500K	3 5 K
4000K	4 0 K
Custom CCT	X X K

F CRI

CRI > 80	C 8 0
CRI > 90	C 9 0

G VOLTAGE

120V / 277V U N V

H DIMMING

0-10V 1% 0 1 0 V
Power over ethernet P O E C
consult customer service for compatibility

I OUTPUT LM/FT DOWN

500lm/ft 100% ↓	0 5 0 0 L F
750lm/ft 100% ↓	0 7 5 0 L F
1000lm/ft 100% ↓	1 0 0 0 L F
Custom lm/ft	X X X X L F

custom lumen up to 1200 lm/ft

J OUTPUT LM/FT UP

500lm/ft ↑	0 5 0 0 L F
750lm/ft ↑	0 7 5 0 L F
1000lm/ft ↑	1 0 0 0 L F
Custom lm/ft	X X X X L F

custom lumen up to 1000 lm/ft

K CIRCUIT / EM

Single circuit	S C
Dual circuit	D C

EMC or EMP not available

L DIAMETER IN INCH

Ø36"	D M - 3 6 I N
Ø48"	D M - 4 8 I N
Ø60"	D M - 6 0 I N
Ø72"	D M - 7 2 I N
Ø96"	D M - 9 6 I N
Ø120"	D M - 1 2 0 I N
Ø240"	D M - 2 4 0 I N

Technical data

DIRECT / INDIRECT



DIAMETER SIZE	ARC LEN MECH	LEDs	ARC LEN EL	LUMEN OUTPUT (LM/FT)	POWER INPUT (W)	EFFICACY (LM/W)	LUMEN OUTPUT (LM/FT)	POWER INPUT (W)	EFFICACY (LM/W)	LUMEN OUTPUT (LM/FT)	POWER INPUT (W)	EFFICACY (LM/W)
D 36"	9.4	480	10	500	41.0	122	750	63.0	119	1000	89.0	112
D 48"	12.6	576	12	500	49.2		750	75.6		1000	106.8	
D 60"	15.7	768	16	500	65.6		750	100.8		1000	142.4	
D 72"	18.8	960	20	500	82.0		750	126.0		1000	178.0	
D 96"	25.1	1152	24	500	98.4		750	151.2		1000	213.6	
D 120"	31.4	1536	32	500	131.2		750	201.6		1000	284.8	
D 240"	62.8	3072	64	500	262.4		750	403.2		1000	569.6	



for 30 K or 35 K multiply lm value by 0.96

DIMENSIONS

FULL CIRCLE DIMENSIONS

NOMINAL	ON-CENTER RADIUS	ON-CENTER DIAMETER	OUTSIDE DIAMETER	OUTSIDE CIRCUMFER.
Ø 36"	18"	Ø 36"	Ø 38 3/8"	120 9/16"
Ø 48"	24"	Ø 48"	Ø 50 3/8"	158 1/4"
Ø 60"	30"	Ø 60"	Ø 62 3/8"	196"
Ø 72"	36"	Ø 72"	Ø 74 3/8"	233 5/8"
Ø 96"	48"	Ø 96"	Ø 92 3/8"	306"
Ø 120"	60"	Ø 120"	Ø 122 3/8"	384 7/16"
Ø 240"	120"	Ø 240"	Ø 242 3/8"	761 7/16"

PENDANT





CURVE/CIRCLE 1.5 2.5 4.0

BASO INC.

Final Assembly: Oxford, Connecticut, USA
Life Expectancy: 5 Year(s)
End of Life Options: Recyclable (70%), Landfill (30%)

Ingredients:

Aluminum alloy; Copper chloride (CuCl₂); 2-Propenoic acid, 3-methyl-, methyl ester, polymer with ethyl 2-propenoate; 3003 Aluminum alloy; Small electrical components¹; Nickel (Metallic); 1040 Carbon steel; Stainless steel, A380 Aluminum alloy; Brass; Silicon; Poly(mimno),6-dioxo-1,6-, hexanediyl(mimno)-1,6-, hexanediyl²; 301 Stainless steel alloy; Acetic acid ethenyl ester, polymer with ethenyl; Copper, Polypropylene; Magnesium hydroxide; Tin, Organic Zinc.

¹LBC Temp Exemption RL-002 - Small Electrical Components

Living Building Challenge Criteria: Compliant

I-13 Red List:

■ LBC Red List: Free ■ LBC Red List: Approved ■ Declared	% Disclosed: 100% at 100ppm - VOC Content: Not Applicable
--	--

I-10 Interior Performance: Not Applicable

I-14 Responsible Sourcing: Not Applicable

BAS-0001
 EXP. 01 JUL 2026
 Original Issue Date: 2022

CIRCLE mounting instructions

Get access to the CIRCLE circle mounting instructions faster by scanning the QR code.

[https://www.basolighting.com/
resources/mounting-instructions/
circle](https://www.basolighting.com/resources/mounting-instructions/circle)

