PANO 3.25"

WOODWORKS®

LINEAR SOLID & VENEERED WOOD PANELS

5 YEAR limited led warranty



MOUNTING

Quick and easy electrical connection

REMOTE MOUNTING

PERFORMANCE

- Up to 122lm/W
- Coordinates with Woodworks® Linear & Veneered ceiling panel
- High performance opal cover
- Remote mountable LED driver
- Damp rated
- Customizable



COMPATIBLE CONTROLS & FEATURES

ATHENA WIRELESS NODE by LUTRON

HLIGHT

SENSOR READY

consult factory

CERTIFICATIONS & COMPLIANCE

cULus

RoHS compliant

Declare. RedList Approved

DIMENSIONS



Catalog Number Example

PANO3-WLV-BL-PS-OP-27K-C80-UNV-010V-0875LF-ST-04FT

A B C D E F G H I J L M

A RANGE

PANO 3.25"	PANO3

B CEILING TYPE

WoodWorks® linear solid wood panels	WLS
WoodWorks® linear veneered panels	WLV

please contact your Armstrong® ceilings rep for the Integrated Light Connection Clip for the specified ceiling type

C COLOR

White	WH
Black	BL

D POWER FEED LENGTH

4' standard integrated	PS
10' medium remote option	PM
30' long remote option	PL

power feed distance denotes secondary wiring from detachable driver box to fixture; driver box comes with a 6ft conduit for primary wiring

E LENS

HP opal cover	OP

F CCT

2700K	27K
3000K	30K
3500K	35K
4000K	40K
Custom CCT	XXK

G CRI

CRI > 80	C80
CRI > 90	C90

H VOLTAGE

120V / 277V	UNV

I DIMMING

0-10V 1%	010V
Lutron EcoSystem Quantum, Vive, GRAFIK Eye, HomeWorks	LES1
Power over ethernet consult customer service for compatibility	POEC
Custom dimming consult customer service for compatibility	XXXX

J OUTPUT LM/FT

450lm/ft 100% ↧	0450LF
675lm/ft 100% ↧	0675LF
875lm/ft 100% ↧	0875LF

K CIRCUIT / EM

Single circuit * leave blank	*
EMB EM battery pack emergency battery pack only for 120/ 277V option (90 minute emergency operation)	EMB

L SHAPE / PATTERN

Linear / straight	ST

M DIMENSIONS IN FT

4' fixture	04FT
6' fixture	06FT
8' fixture	08FT
Custom length Consult Factory	###IN

fixture replaces full length of ceiling panel; please see table on next page and fixture length dimensions

BASO

basolighting.com

Technical data

	SIZE TYPE	LEDCOLOR TEMPERATURE	INPUT WATTS	DELIVERED LMTOTAL	LIGHT DISTRIBUTION	DELIVERED LUMENDIRECT	OPTICAL EFFICIENCY	LUMINAIRE EFFICACY
PANO 3.25"								
e LED	8' opal	40K	29.5W	3600lm	100% down	3600lm	79%	122lm/W
e2LED	8' opal	40K	44.7W	5400lm	100% down	5400lm	79%	121 lm/W
e2+ LED	8' opal	40K	58.9W	7000lm	100% down	7000lm	79%	119lm/W

for 27K, 30K or 35K multiply lm value by 0.96

WoodWorks® Grille Ceiling System Integration

(for more ceiling options, please see CEILING OPTIONS pages)





Available lengths for ceiling types

CEILING TYPE	2FT	4FT	6FT	8FT
WoodWorks® Grille Tegular 9/16	23.375"	47.375"	n/a	n/a
WoodWorks® Grille Tegular 15/16	23"	47"	n/a	n/a
WoodWorks® Grille Classic	23"	47"	71"	95"
WoodWorks® Grille Forte	*23"	47"	71"	95"
WoodWorks® Linear Solid Wood panels	*23"	*47"	*71"	95"
WoodWorks® Linear Veneered panels	*23"	*47"	*71"	95.25"

*Woodworks ceilings are not available in this length. Wood panels need to be cut in the field to fit this length.

WoodWorks® ceiling systems

BASO PANO is only approved for Armstrong® WoodWorks Grille Tegular 9/16, WoodWorks Grille Tegular 15/16, WoodWorks Grille, WoodWorks Linear Solid Wood panels and WoodWorks Linear Veneered panels ceiling systems.
Refer to armstrongceilings.com for installation instructions related to the ceiling products.

PANO 3.25"

WLS - ARMSTRONG® WOODWORKS® LINEAR SOLID WOOD PANELS



WLS view from below



WLV - ARMSTRONG® WOODWORKS® LINEAR VENEERED PANELS



WLV view from below



PANO mounting instructions

Get access to the PANO mounting instructions faster by scanning the QR code.

https://www.basolighting.com/resources/mounting-instructions/pano