



BASO 1.5

DIRECT

CERTIFICATIONS & COMPLIANCE




FEATURES

5 YEAR
limited
led warranty

Declare.
Red List Approved


PERFORMANCE

- Up to 98lm/W efficiency
- 400 /
- CRI > 80 & CRI > 90
- Damp rated



MOUNTING

Ceiling



Pendant



FIELD-CUTTABLE FLEX
Down to 1/16"

[link to video](#)

10 Business Days for all QuickShip items

- Maximum quantity: 400'
- "QuickShip" must be clearly listed on PO.
- QuickShip items must be on Separate Purchase Order.
- QuickShip orders must be received with complete and correct catalog numbers.
- Variant request will not qualify for QuickShip program.
- QuickShip orders must be received before 2 pm EST. After 2 pm, shipping will be based on the next business day.
- QuickShip orders are based on standard BASO Lighting terms for payment.
- Order change of any type will affect shipping times.
- Partial shipments may be required based on current factory inventory.

Catalog Number Example

BASO1.5-PDT-BL-30K-C80-UNV-010V-0400LF-ST-48IN

A B C D E F G H J K

A RANGE

QS BASO 1.5 BASO 1.5

B MOUNTING

QS Surface SUR

QS Pendant PDT

pendant suspension set includes cable suspension and one white power feeder with a white junction box cover

for black power feeds or junction box covers, please contact customer service

C COLOR

QS White WH

QS Black BL

D CCT

QS 3000K 30K

QS 3500K 35K

E CRI

QS CRI > 80 C80

QS CRI > 90 C90

F VOLTAGE

QS 120V / 277V UNV

G DIMMING

QS 0-10V 1% 010V

H OUTPUT LM/FT

QS 400lm/ft 100% 0400LF

QS 600lm/ft 100% 0600LF

QS 800lm/ft 100% 0800LF

I CIRCUIT / EM

QS Single circuit *

J SHAPE / PATTERN

QS Linear / straight ST

QS Linear / straight + flex inset SF
includes 1ft. field-cutable section; only available for 4' and 8' segments

K DIMENSIONS IN INCH

QS Linear 4' 48IN

QS Linear 6' 72IN

QS Linear 8' 96IN

QS Custom length XXFT
(QS in 2' increments only)

Technical data

BASO 1.5 DIRECT

LUMEN OUTPUT MULTIPLIER*

Color Temperature

CRI


Delivered Lumens	CCT	CRI	Input Watts	Luminaire Efficacy	4000K	80+	90+
400 lm/ft ↓	4000K	CRI > 80	3.9 W/ft	103 lm/W	3500K	1	0.86
600 lm/ft ↓	4000K	CRI > 80	5.9 W/ft	102 lm/W	3000K	0.96	0.84
800 lm/ft ↓	4000K	CRI > 80	8.2 W/ft	98 lm/W	2700K	0.95	0.82
						0.91	0.78

*To calculate the color temperatures >4000K and CRI 90, multiply the values in the lumen output tables.

Patterns top view

LINEAR



A	FIXTURES	CODE
48"	1 × 4' linear	ST - 0 4 FT
96"	1 × 8' linear	ST - 0 8 FT
144"	8' + 4' linear	ST - 1 2 FT



BASO 1.5

SURFACE





direct



PENDANT

direct

direct / indirect



BASO mounting instructions

Get access to the BASO 1.5 mounting instructions faster by scanning the QR code.

<https://www.basolighting.com/resources/mounting-instructions/baso>

