




# BASO 1.5

## WALL WASH



### CERTIFICATIONS & COMPLIANCE




### FEATURES

**5 YEAR**  
limited  
led warranty

**Declare.**  
Red List Approved


### PERFORMANCE

- Up to 103lm/W efficiency
- 400 / 600 / 800lm/ft
- CRI > 80 & CRI > 90
- Damp rated



### MOUNTING

Ceiling



Suspended



### Catalog Number Example

BASO1.5-SUR-BL-WW-30K-C80-UNV-010V-0400LF-0400LF-ST-48IN

A B C D E F G H I J L M

### A RANGE

QS BASO 1.5 BASO 1.5

### B MOUNTING

QS Surface SUR

QS Pendant PDT

### C COLOR

QS White WH

QS Black BL

### D LENS

QS Asymmetric wall washer WW

### E CCT

QS 3000K 30K

QS 3500K 35K

### F CRI

QS CRI > 80 C80

QS CRI > 90 C90

### G VOLTAGE

QS 120V / 277V UNV

### H DIMMING

QS 0-10V 1% 010V

### I OUTPUT LM/FT DOWN

QS 400lm/ft ↓ 0400LF

QS 600lm/ft ↓ 0600LF

800lm/ft ↓ 0800LF

Custom lm/ft XXXXLF

custom lumen up to 800 lm/ft

### J OUTPUT LM/FT UP

QS 400lm/ft ↑ 0400LF

QS 600lm/ft ↑ 0600LF

QS 800lm/ft ↑ 0800LF

Custom lm/ft XXXXLF

custom lumen up to 1000 lm/ft

### K CIRCUIT / EM

QS Single circuit \*

### L SHAPE / PATTERN

QS Linear / straight ST

QS Linear / straight + flex inset SF

includes 1ft. field-cutable section; only

available for 4' and 8' segments

### M DIMENSIONS IN INCH

QS Linear 4' 48IN

QS Linear 6' 72IN

QS Linear 8' 96IN

QS Custom length XXFT

(QS in 2' increments only)

### 10 Business Days for all QuickShip items

- Maximum quantity: 400'
- "QuickShip" must be clearly listed on PO.
- QuickShip items must be on Separate Purchase Order.
- QuickShip orders must be received with complete and correct catalog numbers.
- Variant request will not qualify for QuickShip program.
- QuickShip orders must be received before 2 pm EST. After 2 pm, shipping will be based on the next business day.
- QuickShip orders are based on standard BASO Lighting terms for payment.
- Order change of any type will affect shipping times.
- Partial shipments may be required based on current factory inventory.

## Technical data

### BASO 1.5 DIRECT

#### LUMEN OUTPUT MULTIPLIER\*

Color Temperature	CRI	
	80+	90+
4000K	1	0.86
3500K	0.96	0.84
3000K	0.95	0.82
2700K	0.91	0.78

Delivered Lumens	CCT	CRI	Input Watts	Luminaire Efficacy
400 lm/ft ↓	4000K	CRI > 80	3.9 W/ft	103 lm/W
600 lm/ft ↓	4000K	CRI > 80	5.9 W/ft	102 lm/W
800 lm/ft ↓	4000K	CRI > 80	8.2 W/ft	98 lm/W

\*To calculate the color temperatures >4000K and CRI 90, multiply the values in the lumen output tables.

## Patterns top view


### LINEAR



A	FIXTURES	CODE
48"	1'× 4' linear	ST - 0 4 FT
96"	1'× 8' linear	ST - 0 8 FT
144"	8' + 4' linear	ST - 1 2 FT



## BEAM DISTRIBUTION

### Wall to ceiling ratio

Room height	H = 9 ft
Distance to wall	A = 3 ft
Reflection factor	0.7   0.5   0.2
Maintenance factor	0.8
Eye level 	4 – 5 ft



## BASO mounting instructions

Get access to the BASO 1.5 mounting instructions faster by scanning the QR code.


<https://www.basolighting.com/resources/mounting-instructions/baso>






## DIMENSIONS

### BASO 1.5 WALL WASHER

CEILING direct



PENDANT direct



### BASO mounting instructions

Get access to the BASO 1.5 mounting instructions faster by scanning the QR code.

<https://www.basolighting.com/resources/mounting-instructions/baso>

