




BASO 2.5 DIRECT



CERTIFICATIONS & COMPLIANCE




FEATURES




PERFORMANCE

- Up to 106lm/W efficiency
- 455 / 750lm/ft
- CRI > 80 & CRI > 90
- IC & Damp rated



MOUNTING

Recessed



FIELD-CUTTABLE FLEX
Down to 1/16"

[link to video](#)

10 Business Days for all QuickShip items

- Maximum quantity: 400'
- "QuickShip" must be clearly listed on PO.
- QuickShip items must be on Separate Purchase Order.
- QuickShip orders must be received with complete and correct catalog numbers.
- Variant request will not qualify for QuickShip program.
- QuickShip orders must be received before 2 pm EST. After 2 pm, shipping will be based on the next business day.
- QuickShip orders are based on standard BASO Lighting terms for payment.
- Order change of any type will affect shipping times.
- Partial shipments may be required based on current factory inventory.

Catalog Number Example

BASO2.5-RTR-BL-30K-010V-C80-UNV-0500LF-ST-48IN

A B C D E F G H I K

A RANGE

QS BASO 2.5 BASO2.5

G VOLTAGE

QS 120V / 277V UNV

B MOUNTING

QS Recessed trimless R T L
 QS Recessed with trim R T R
 QS 9/16" Grid (any brand) 9 G R
 QS 9/16" Slot Grid (any brand) 9 S G
 QS 15/16" Grid (any brand) 1 5 G

J OUTPUT LM/FT

QS 500lm/ft 100% ‡ 0 5 0 0 L F
 QS 750lm/ft 100% ‡ 0 7 5 0 L F
 QS 1000lm/ft 100% ‡ 1 0 0 0 L F
 Custom lm/ft X X X X L F
custom lumen up to 1200 lm/ft

C COLOR

QS White WH
 QS Black B L

I CIRCUIT / EM

QS Single circuit *

D CCT

QS 3000K 3 0 K
 QS 3500K 3 5 K

J SHAPE / PATTERN

QS Linear / straight S T
 QS Linear / straight + flex inset S F
includes 1ft. field-cutttable section; only available for 4' and 8' segments

E DIMMING

QS 0-10V 1% 0 1 0 V

F CRI

QS CRI > 80 C 8 0
 QS CRI > 90 C 9 0

K DIMENSIONS IN INCH

QS Linear 4' 4 8 I N
 QS Linear 6' 7 2 I N
 QS Linear 8' 9 6 I N
 QS Custom length X X F T
(QS in 2' increments only)

Technical data

BASO 2.5 DIRECT

LUMEN OUTPUT MULTIPLIER*

Color Temperature	CRI	
	80+	90+
4000K	1	0.86
3500K	0.96	0.84
3000K	0.95	0.82
2700K	0.91	0.78

Delivered Lumens	CCT	CRI	Input Watts	Luminaire Efficacy
500 lm/ft †	4000K	CRI > 80	4.1 W/ft	122 lm/W
750 lm/ft †	4000K	CRI > 80	6.3 W/ft	119 lm/W
1000 lm/ft †	4000K	CRI > 80	8.9 W/ft	112 lm/W

*To calculate the color temperatures >4000K and CRI 90, multiply the values in the lumen output tables.

Patterns top view

LINEAR

	FIXTURES	CODE
48"	1'x 4' linear	ST - 0 4 FT
96"	1'x 8' linear	ST - 0 8 FT
144"	8'+ 4' linear	ST - 1 2 FT



