

CERTIFICATIONS & COMPLIANCE



FEATURES



PERFORMANCE

- 48V low voltage track
- Multiple inset options available
- CRI > 90+
- Flexible magnetic profile system

MOUNTING

Ceiling

Pendant





10 Business Days for all QuickShip items

- Maximum quantity: 400'
- · "QuickShip" must be clearly listed on PO.
- · QuickShip items must be on Separate Purchase Order.
- QuickShip orders must be received with complete and correct catalog numbers.
- Variant request will not qualify for QuickShip program.
- QuickShip orders must be received before 2 pm EST. After 2 pm, shipping will be based on the next business day.
- QuickShip orders are based on standard BASO Lighting terms for payment.
- Order change of any type will affect shipping times.
- Partial shipments may be required based on current factory inventory.

Catalog Number Example

MLINS1.1-SUR-BL-48V-010V-ST-04FT



A RANGE

 Image: M-LINE 1.1
 M L I N S 1 . 1

 Image: M-LINE 1.2
 M L I N S 1 . 2

B MOUNTING

 Surface mount
 S U R

 Pendant
 P D T

 pendant suspension set includes cable

 suspension and one white J-box cover

COLOR outside / inside

Black B L

D VOLTAGE

Constant voltage track 48 V

G SHAPE / PATTERN

QS	Linear	S	Т

G DIMENSIONS IN FEET


os Linear 4'	04FT
Linear 8'	08FT
OS Custom length	XXFT
(QS in 2' increments only)	




M-LINE 1.1 channel dimensions

CEILING

PENDANT





Possible shapes top view

please provide RCP to ensure correct shape orientation


LINEAR

Power feeder locations

POWER FEED



LINEAR POWER COUPLER



M-LINE Mounting Instructions

Get access to the M-LINE mounting instructions faster by scanning the QR code.

https://www.basolighting.com/ resources/mounting-instructions/ m-line

