



CERTIFICATIONS & COMPLIANCE



FEATURES

5 YEAR limited led warranty

PERFORMANCE

- SPOT 32 beam angle 17° 43°
- Up to 400 Im output Magnetic inset attachment
- CRI > 90
- Safety catch locking
- Honeycomb louver accessories

INSET TYPE SPOT 32 FOCUS



10 Business Days for all QuickShip items

- Maximum quantity: 50 pieces
- "QuickShip" must be clearly listed on PO.
- QuickShip items must be on Separate Purchase Order.
- QuickShip orders must be received with complete and correct catalog numbers.
- · Variant request will not qualify for QuickShip program.
- QuickShip orders must be received before 2 pm EST. After 2 pm, shipping will be based on the next business day.
- QuickShip orders are based on standard BASO Lighting terms for payment.
- · Order change of any type will affect shipping times.
- Partial shipments may be required based on current factory inventory.

Catalog Number Example

MLINS-SPOT32-BL-30K-C90-010V-0400LM

A	RANGE
08	M LINE incot

 MLINE inset
 MLINS

• 0-10V 1% single control 0 1 0 V

INSET TYPE

SPOT 32 FOCUS SPOT 3 2 17° - 43° beam angle

G OUTPUT LM

ES 400 / 9 W 0 4 0 0 L M SPOT 32

G COLOR

OS Black B L

Осст

 Image: Signal state
 Signal

M-LINE Mounting Instructions

Get access to the M-LINE mounting instructions faster by scanning the QR code.

https://www.basolighting.com/ resources/mounting-instructions/ m-line









CERTIFICATIONS & COMPLIANCE



FEATURES

5 YEAR limited led warranty

PERFORMANCE

- Beam angle 14°, 23°, 36° or 60°
- Magnetic inset attachment
- CRI > 90
- · Safety catch locking

INSET TYPE

SPOT 55



10 Business Days for all QuickShip items

- Maximum quantity: 50 pieces
- "QuickShip" must be clearly listed on PO.
- QuickShip items must be on Separate Purchase Order.
- QuickShip orders must be received with complete and correct catalog numbers.
- Variant request will not qualify for QuickShip program.
- QuickShip orders must be received before 2 pm EST. After 2 pm, shipping will be based on the next business day.
- QuickShip orders are based on standard BASO Lighting terms for payment.
- Order change of any type will affect shipping times.
- Partial shipments may be required based on current factory inventory.

Catalog Number Example

MLINS-SPOT55-BL-30K-C90-SP-010V-0700LM

R

S M-LINE inset	MLINS						

INSET TYPE SPOT 55 SPOT55

os 36° flood € 60° wide flood*

os 14° spot

os 23° medium

O DIMMING

G LIGHT DISTRIBUTION

0-10V 1% single control 010V

SΡ

ΜD

FL

WΙ

ΒL

Осст			
os 3000 K	3 0 K		
QS 3500 K	3 5 K		

OUTPUT LM 700 lm / 11 W

QS	700 lm / 11 W	0	7	0	0	L	Μ

CRI

G COLOR

os Black

```
CRI > 90
                        C 9 0
```

M-LINE Mounting Instructions

Get access to the M-LINE mounting instructions faster by scanning the QR code.

https://www.basolighting.com/ resources/mounting-instructions/ m-line



