




PANO 2"

WOODWORKS® GRILLE CLASSIC



CERTIFICATIONS & COMPLIANCE




FEATURES




PERFORMANCE

- Lengths coordinates with Woodworks® Grille ceiling panel
- Up to 109lm/W
- High performance opal cover
- Remote mountable LED driver
- Damp rated



WoodWorks® Grille Ceiling System Integration



REMOTE MOUNTING

Quick and easy electrical connection

REMOTE MOUNTING



Catalog Number Example

PANO2-WWG-WH-PS-OP-27K-C80-UNV-010V-0425LF-ST-08FT



A RANGE

PANO 2" PANO 2

H VOLTAGE

120V / 277V UNV

B CEILING TYPE

WoodWorks® Grille WWG

please contact your Armstrong® ceilings rep for the Integrated Light Connection Clip for the specified ceiling type

I DIMMING

0-10V 1% 0 1 0 V

J OUTPUT LM/FT

425 lm/ft 100% 0 4 2 5 L F

C COLOR

Black B L

K SHAPE / PATTERN

Linear / straight S T

D POWER FEED LENGTH

4' standard integrated P S

E LENS

HP opal cover O P

F CCT

3000 K 3 0 K
3500 K 3 5 K

L DIMENSIONS IN FT

4' fixture 0 4 F T
6' fixture 0 6 F T
8' fixture 0 8 F T

fixture replaces full length of ceiling panel; please see table on next page and fixture length dimensions

G CRI

CRI > 80 C 8 0
CRI > 90 C 9 0


Technical data

	SIZE TYPE	LED COLOR TEMPERATURE	INPUT WATTS	DELIVERED LM TOTAL	LIGHT DISTRIBUTION	DELIVERED LUMEN DIRECT	OPTICAL EFFICIENCY	LUMINAIRE EFFICACY
PANO 2"								
e LED	8' opal	40 K	20.3 W	2200 lm	100 % down	2200 lm	70 %	108 lm/W
e ² LED	8' opal	40 K	31.2 W	3400 lm	100 % down	3400 lm	70 %	109 lm/W
e ²⁺ LED	8' opal	40 K	44.7 W	4800 lm	100 % down	4800 lm	70 %	107 lm/W

for 27 K, 30 K or 35 K multiply lm value by 0.96

WoodWorks® Grille Ceiling System Integration

(for more ceiling options, please see CEILING OPTIONS pages)



Available lengths for ceiling types

CEILING TYPE	2 FT	4 FT	6 FT	8 FT
WoodWorks® Grille Tegular $\frac{9}{16}$	23.375"	47.375"	n/a	n/a
WoodWorks® Grille Tegular $\frac{15}{16}$	23"	47"	n/a	n/a
WoodWorks® Grille Classic	23"	47"	71"	95"
WoodWorks® Grille Forte	*23"	47"	71"	95"
WoodWorks® Linear Solid Wood panels	*23"	*47"	*71"	95"
WoodWorks® Linear Veneered panels	*23"	*47"	*71"	95.25"

*Woodworks ceilings are not available in this length. Wood panels need to be cut in the field to fit this length.

INTEGRATED LIGHT CONNECTION CLIP

Armstrong® Ceilings Integrated Light
Connection Clip

please contact your Armstrong Ceilings rep

visit
[armstrongceilings.com](http://armstrongceilings.com/linearlighting)
[/linearlighting](http://armstrongceilings.com/linearlighting)

WoodWorks® ceiling systems

BASO PANO is only approved for Armstrong® WoodWorks Grille Tegular 9/16, WoodWorks Grille Tegular 15/16, WoodWorks Grille, WoodWorks Linear Solid Wood panels and WoodWorks Linear Veneered panels ceiling systems. Refer to armstrongceilings.com for installation instructions related to the ceiling products.







DIMENSIONS





PANO 2"

WWG - ARMSTRONG® WOODWORKS® GRILLE PANELS

WWG view from below



WWG - ARMSTRONG® WOODWORKS® GRILLE PANELS cont'd



PANO mounting instructions

Get access to the PANO mounting instructions faster by scanning the QR code.

<https://www.basolighting.com/resources/mounting-instructions/pano>

