




PANO 3.25"

WOODWORKS®

GRILLE TEGULAR 9/16" & 15/16" INTEGRATION



CERTIFICATIONS & COMPLIANCE




FEATURES




PERFORMANCE

- Coordinates with Woodworks® Grille Tegular & integration ceiling panel
- Up to 122lm/W
- High performance opal cover
- Remote mountable LED driver
- Damp rated



WoodWorks® Grille Tegular Ceiling Integration

Grille Tegular Panel



REMOTE MOUNTING

Quick and easy electrical connection



Catalog Number Example

PANO3-WT9-WH-PS-OP-27K-C80-UNV-010V-0450LF-ST-02FT



A RANGE

PANO 3.25" PANO 3

H VOLTAGE

120V / 277V UNV

B CEILING TYPE

WoodWorks® Grille Tegular 9/16" WT 9

WoodWorks® Grille Tegular 15/16" WT 5

please contact your Armstrong® ceilings rep for the Integrated Light Connection Clip for the specified ceiling type

I DIMMING

0-10V 1% 0 1 0 V

J OUTPUT LM/FT

675lm/ft 100% 0 6 7 5 L F

K SHAPE / PATTERN

Linear / straight ST

C COLOR

Black BL

D POWER FEED LENGTH

4' standard integrated PS

L DIMENSIONS IN FT

2' fixture 0 2 F T

4' fixture 0 4 F T

fixture replaces full length of ceiling panel slats; please see table on next page and fixture length dimensions

E LENS

HP opal cover OP

F CCT

3000K 3 0 K

3500K 3 5 K

G CRI

CRI > 80 C 8 0

CRI > 90 C 9 0


Technical data

	SIZE TYPE	LED COLOR TEMPERATURE	INPUT WATTS	DELIVERED LM TOTAL	LIGHT DISTRIBUTION	DELIVERED LUMEN DIRECT	OPTICAL EFFICIENCY	LUMINAIRE EFFICACY
PANO 3.25" e LED	2' opal	40 K	8 W	900 lm	100 % down	900 lm	73 %	116 lm/W
	4' opal		15.9 W	1800 lm		1800 lm		116 lm/W
e ² LED	2' opal	40 K	12.3 W	1350 lm	100 % down	1350 lm	73 %	111 lm/W
	4' opal		24.6 W	2700 lm		2700 lm		111 lm/W
e ²⁺ LED	2' opal	40 K	16.4 W	1750 lm	100 % down	1750 lm	73 %	108 lm/W
	4' opal		32.7 W	3500 lm		3500 lm		108 lm/W

for 27 K, 30 K or 35 K multiply lm value by 0.96

WoodWorks® Grille Tegular Ceiling Integration

(for more ceiling options, please see CEILING OPTIONS pages)



Available lengths for ceiling types

CEILING TYPE	2 FT	4 FT	6 FT	8 FT
WoodWorks® Grille Tegular 9/16	23.375"	47.375"	n/a	n/a
WoodWorks® Grille Tegular 15/16	23"	47"	n/a	n/a
WoodWorks® Grille Classic	23"	47"	71"	95"
WoodWorks® Grille Forte	*23"	47"	71"	95"
WoodWorks® Linear Solid Wood panels	*23"	*47"	*71"	95"
WoodWorks® Linear Veneered panels	*23"	*47"	*71"	95.25"

*Woodworks ceilings are not available in this length. Wood panels need to be cut in the field to fit this length.

INTEGRATED LIGHT CONNECTION CLIP

Armstrong® Ceilings Integrated Light
Connection Clip

please contact your Armstrong Ceilings rep

visit
[armstrongceilings.com](https://armstrongceilings.com/linearlighting)
[/linearlighting](https://armstrongceilings.com/linearlighting)

WoodWorks® ceiling systems

BASO PANO is only approved for Armstrong® WoodWorks Grille Tegular 9/16, WoodWorks Grille Tegular 15/16, WoodWorks Grille, WoodWorks Linear Solid Wood panels and WoodWorks Linear Veneered panels ceiling systems. Refer to armstrongceilings.com for installation instructions related to the ceiling products.






DIMENSIONS

PANO 3.25"

WT9 - ARMSTRONG® WOODWORKS® GRILLE TEGULAR $\frac{9}{16}$ PANELS

WT9 view from below









PANO 3.25"

WT5 - ARMSTRONG® WOODWORKS® GRILLE TEGULAR $1\frac{5}{16}$ PANELS

WT5 view from below



PANO mounting instructions

Get access to the PANO mounting instructions faster by scanning the QR code.

<https://www.basolighting.com/resources/mounting-instructions/pano>

