


PANO 3.25"

WOODWORKS® GRILLE CLASSIC



CERTIFICATIONS & COMPLIANCE




FEATURES




PERFORMANCE

- Coordinates with Woodworks® Grille ceiling panel
- Up to 122lm/W
- High performance opal cover
- Remote mountable LED driver
- Damp rated



WoodWorks® Grille Ceiling Integration



REMOTE MOUNTING

Quick and easy electrical connection

REMOTE MOUNTING



Catalog Number Example

PANO3-WWG-WH-PS-OP-30K-C80-UNV-010V-0675LF-ST-08FT



A RANGE PANO 3.25" PANO3	H VOLTAGE 120V / 277V UNV
B CEILING TYPE WoodWorks® Grille WWG please contact your Armstrong® ceilings rep for the Integrated Light Connection Clip for the specified ceiling type	I DIMMING 0-10V 1% 0 1 0 V
C COLOR Black BL	J OUTPUT LM/FT 675lm/ft 100% ↓ 0 6 7 5 L F
D POWER FEED LENGTH 4' standard integrated PS	K SHAPE / PATTERN Linear / straight ST
E LENS HP opal cover OP	L DIMENSIONS IN FT 4' fixture 0 4 F T 6' fixture 0 6 F T 8' fixture 0 8 F T fixture replaces full length of ceiling panel; please see table on next page and fixture length dimensions
F CCT 3000K 3 0 K 3500K 3 5 K	
G CRI CRI > 80 C 8 0 CRI > 90 C 9 0	


Technical data

	SIZE TYPE	LED COLOR TEMPERATURE	INPUT WATTS	DELIVERED LM TOTAL	LIGHT DISTRIBUTION	DELIVERED LUMEN DIRECT	OPTICAL EFFICIENCY	LUMINAIRE EFFICACY
PANO 3.25"								
e LED	8' opal	40K	29.5 W	3600 lm	100% down	3600 lm	79%	122 lm/W
e ² LED	8' opal	40K	44.7 W	5400 lm	100% down	5400 lm	79%	121 lm/W
e ²⁺ LED	8' opal	40K	58.9 W	7000 lm	100% down	7000 lm	79%	119 lm/W

for 27 K, 30K or 35K multiply lm value by 0.96

WoodWorks® Grille Ceiling Integration

(for more ceiling options, please see CEILING OPTIONS pages)



Available lengths for ceiling types

CEILING TYPE	2 FT	4 FT	6 FT	8 FT
WoodWorks® Grille Tegular 9/16	23.375"	47.375"	n/a	n/a
WoodWorks® Grille Tegular 15/16	23"	47"	n/a	n/a
WoodWorks® Grille Classic	23"	47"	71"	95"
WoodWorks® Grille Forte	*23"	47"	71"	95"
WoodWorks® Linear Solid Wood panels	*23"	*47"	*71"	95"
WoodWorks® Linear Veneered panels	*23"	*47"	*71"	95.25"

*Woodworks ceilings are not available in this length. Wood panels need to be cut in the field to fit this length.

INTEGRATED LIGHT CONNECTION CLIP

Armstrong® Ceilings Integrated Light Connection Clip

visit armstrongceilings.com/linearlighting

please contact your Armstrong Ceilings rep

WoodWorks® ceiling systems







BASO PANO is only approved for Armstrong® WoodWorks Grille Tegular 9/16, WoodWorks Grille Tegular 15/16, WoodWorks Grille, WoodWorks Linear Solid Wood panels and WoodWorks Linear Veneered panels ceiling systems. Refer to armstrongceilings.com for installation instructions related to the ceiling products.

DIMENSIONS



PANO 3.25"

WWG - ARMSTRONG® WOODWORKS® GRILLE PANELS

WWG view from below



WWG - ARMSTRONG® WOODWORKS® GRILLE PANELS cont'd



PANO mounting instructions

Get access to the PANO mounting instructions faster by scanning the QR code.

<https://www.basolighting.com/resources/mounting-instructions/pano>

