X-LITE™
DIRECT



CERTIFICATIONS & COMPLIANCE

c UL us | RoHS compliant | TITLE 24 JA8

FEATURES

5 YEAR limited led warranty | PoE Power over Ethernet | QS

PERFORMANCE

- Up to 70 lm/W
- Multipurpose lighting system
- Multiple lens and housing options
- Recessed, surface, suspended



HOUSING OPTIONS

SN- 1x1

ST-1x3



ST-1x2

ST-1x4



SQ-2x2



SQ- 3x3



SIDE VIEW



*HEIGHT IS 3" FOR ALL MOUNTING TYPES

DIMENSIONS

Spot



Wallwash



Specification/Instructions

Use the drop downs to select each cells attribute.

1. Select mounting type, housing color, color temperature, and cell color
2. Select Dim config for cell formation
3. Cell attribute will auto fill depending on selection made for each cell.

Mounting	Housing Color
Color temp	**Cell Color**

Dim Config: E

A		B	
1	1	1	2
1	1	1	2

C		D		E	
1	2	1	2	1	2
2	1	3	1	3	4

Cell 1	Cell 2
Lens	Lens
DIM Config.	DIM Config.
NOTES	NOTES
Cell 3	**Cell 4**
Lens	Lens
DIM Config.	DIM Config.
NOTES	NOTES

Attributes Key

Use the housing and cell attributes key.

Dim Config: E

E	
1	2
3	4

Housing Attributes Key

A	**RANGE**	
	XLITE	X L I T E
B	**PATTERN**	
	Single 1x1	S N 1 x 1
	Straight 1x2	S T 1 x 2
	Straight 1x3	S T 1 x 3
	Straight 1x4	S T 1 x 4
	Square 2x2	S Q 2 x 2
	Square 3x3	S Q 3 x 3
C	**MOUNTING**	
	Recessed Trimless	R T L
	Recessed Trim	R T R
	Surface Mounted	S U R
	Pendant	P D T
D	**HOUSING COLOR**	
	White	W H
	Black	B L
	Gray	G R
	*RTL in white only	
E	**E DIMMING CHANNEL**	
	single channel	C 1
	dual channel	C 2
	three channel	C 3
	four channel	C 4

Cell Attributes Key

A	**CELL TRIM COLOR**	
	Black Gloss	B G
	Black Matte	B M
	Chrome	C H
	White Gloss	W G
	White Matte	W M
B	**CELL LENS**	
	Spot 14 deg	S P
	Medium 24 deg	M D
	Flood 36 deg	F L
	Wide 60 deg	W I
	Wall Wash Up	W U
	Wall Wash Down	W D
	Wall Wash Left	W L
	Wall Wash Right	W R
	Blind Cover	B C
C	**CELL COLOR TEMPERATURE**	
	2700K CRI 90	2 7
	3000K CRI 90	3 0
	3500K CRI 90	3 5
	4000K CRI 90	4 0
D	**CELL DIMMING CHANNEL**	
	Channel 1	C 1
	Channel 2	C 2
	Channel 3	C 3
	Channel 4	C 4

Housing attributes: XLITE-SQ2x2---

Cell attributes:

Cell 1	Cell 2
WG WL 27 C1	WG SP 35 C2
Cell 3	**Cell 4**
WG SP 35 C3	WG WR 27 C4

Diagram Example

TOP ROW: Cells 1-2
Cell 1: White Gloss cell color, Wall Wash, light shinning left, and 2700K CRI 90 temp.
Cell 2: White Gloss, Spotlight, 3500K CRI 90 temp.

SECOND ROW: Cells 3-4
Cell 3: White Gloss, Spotlight, 3500K CRI 90 temp.
Cell 4: White Gloss cell color, Wall Wash, light shinning right, and 2700K CRI 90 temp.



BASO
basolighting.com

X-LITE™
ST 1X3



CERTIFICATIONS & COMPLIANCE

c UL us · RoHS compliant · TITLE 24 JA8

FEATURES

5 YEAR limited led warranty · PoE Power over Ethernet · QS

PERFORMANCE

- Up to 70lm/W efficiency
- Multiple lens options
- Recessed, surface & pendant
- CRI > 90



DIAGRAM



*Spot and Wallwash cells must have separate dimming channels.

SINGLE CELL LIGHT DISTRIBUTIONS

SPOT LENS 14°



C0/C180 ——
C90/C270 ·····

LED array 2.3W / 245lm
106 lm/W

MEDIUM LENS 30°



C0/C180 ——
C90/C270 ·····

LED array 2.3 W / 225 lm
98 lm/W

FLOOD LENS 36°



C0/C180 ——
C90/C270 ·····

LED array 2.3 W / 235 lm
101 lm/W

WIDE LENS 57°



C0/C180 ——
C90/C270 ·····

LED array 2.3 W / 215 lm
93 lm/W

WALL WASH



C0/C180 ——
C90/C270 ·····

LED array 4.9 W / 365 lm
75 lm/W

MOUNTING

Mounting

HOUSING COLOR

Housing Color
*RTL in white only

COLOR TEMP

Color Temp

CELL COLOR

Cell Color

DIM CONFIG.

Dimming

A	B	C	D
1 1 1	1 2 1	1 2 2	1 2 3

Cell 1	Cell 2	Cell 3
LENS: Optic 2	LENS: Optic 2	LENS: Optic 3
DIM CONFIG.: Select from Above	DIM CONFIG.: Select from Above	DIM CONFIG.: Select from Above
NOTES	NOTES	NOTES

Housing attributes

XLITE-ST1x3-XXX-XX-XX
(A) (B) (C) (D) (E)

Cell attributes

Cell 1: XX XX XX XX (A B C D)
Cell 2: XX XX XX XX (A B C D)
Cell 3: XX XX XX XX (A B C D)

BASO
basolighting.com

Housing Configu ation Code
XLITES30xxx00

Cell Configu ation Code
XCS3xxx00xxx0

Power supply

1. LINE CONTROL

X-LITE 0-10V POWER SUPPLIES

	SPOT CELLS	WALLWASH CELLS
1 cell	XLPS-12-SP-001	XLPS-12-WW-001
2 cell	XLPS-12-SP-002	XLPS-12-WW-002
3 cell	XLPS-12-SP-003	XLPS-12-WW-003
4 cell	XLPS-12-SP-004	XLPS-12-WW-004
5 cell	XLPS-12-SP-005	XLPS-12-WW-005
6 cell	XLPS-12-SP-006	XLPS-12-WW-006
7 cell	XLPS-12-SP-007	XLPS-12-WW-007
8 cell	XLPS-12-SP-008	XLPS-12-WW-008
9 cell	XLPS-12-SP-009	XLPS-12-WW-009

***X-Lite configurations with both Spot and Wallwash cells will need two separate remote drivers**



Wiring diagrams

1. LINE CONTROL

0-10 V DIM Single Cir cuit



0-10V DIM Dual Circuit



0-10 V DIM T ri Circuit



Wiring diagrams continued

0-10 V DIM Quad Cir cuit



Length range per power supply

POWER SUPPLY	
Length A	max 150'





Mounting instructions

Get access to the mounting instructions faster by scanning the QR code.

https://www.basolighting.com/resources/mounting-instructions/x-lite