




M-LINE

SPOT 32



CERTIFICATIONS & COMPLIANCE



FEATURES

5 YEAR
limited
led warranty

PERFORMANCE

- SPOT 32 beam angle 17° - 43°
- Up to 400 lm output
- Magnetic inset attachment
- CRI > 90
- Safety catch locking
- Honeycomb louver accessories

INSET TYPE

SPOT 32 FOCUS



10 Business Days for all QuickShip items

- Maximum quantity: 50 pieces
- "QuickShip" must be clearly listed on PO.
- QuickShip items must be on Separate Purchase Order.
- QuickShip orders must be received with complete and correct catalog numbers.
- Variant request will not qualify for QuickShip program.
- QuickShip orders must be received before 2 pm EST. After 2 pm, shipping will be based on the next business day.
- QuickShip orders are based on standard BASO Lighting terms for payment.
- Order change of any type will affect shipping times.
- Partial shipments may be required based on current factory inventory.

Catalog Number Example

MLINS-SPOT32-BL-30K-C90-010V-0400LM

A B C D E F G

A RANGE

QS M-LINE inset ML I N S

F DIMMING

QS 0-10V 1% single control 0 1 0 V

B INSET TYPE

QS SPOT 32 FOCUS S P O T 3 2
17° - 43° beam angle

G OUTPUT LM

QS 400 / 9 W 0 4 0 0 L M
SPOT 32

C COLOR

QS Black B L

D CCT

QS 3000 K 3 0 K
QS 3500 K 3 5 K



M-LINE

SPOT 55



CERTIFICATIONS & COMPLIANCE



FEATURES


5 YEAR
limited
led warranty

PERFORMANCE

- Beam angle 14°, 23°, 36° or 60°
- Magnetic inset attachment
- CRI > 90
- Safety catch locking

INSET TYPE

SPOT 55



10 Business Days for all QuickShip items

- Maximum quantity: 50 pieces
- "QuickShip" must be clearly listed on PO.
- QuickShip items must be on Separate Purchase Order.
- QuickShip orders must be received with complete and correct catalog numbers.
- Variant request will not qualify for QuickShip program.
- QuickShip orders must be received before 2 pm EST. After 2 pm, shipping will be based on the next business day.
- QuickShip orders are based on standard BASO Lighting terms for payment.
- Order change of any type will affect shipping times.
- Partial shipments may be required based on current factory inventory.

Catalog Number Example

MLINS-SPOT55-BL-30K-C90-SP-010V-0700LM

A B C D E F G H

A RANGE

QS M-LINE inset MLINS

B INSET TYPE

QS SPOT 55 SPOT55

C COLOR

QS Black BL

D CCT

QS 3000 K 30K

QS 3500 K 35K

E CRI

QS CRI > 90 C90

F LIGHT DISTRIBUTION

QS 14° spot SP

QS 23° medium MD

QS 36° flood FL

QS 60° wide flood* WI

G DIMMING

QS 0-10V 1% single control 010V

H OUTPUT LM

QS 700 lm / 11 W 0700LM

M-LINE Mounting Instructions

Get access to the M-LINE mounting instructions faster by scanning the QR code.

<https://www.basolighting.com/resources/mounting-instructions/m-line>



BASO
basolighting.com